



Care and Cleaning of the Panel Outer Surface

Cleaning

- Dust and clean the surface with a soft, damp cloth or chamois. Do not use cloths containing grit, abrasives or kitchen scouring compounds.
- Clean using mild detergents or most household cleaners. Strong soaps or abrasive cleaners should not be used. Refer to the charts below.
- The surface may be waxed with one of the recommended waxes listed below. The surface must be cleaned by washing first.

Surface Repair

- Ground-In Dirt & Grease - normal liquid cleaners or soap/water may not remove this type of dirt. Janitor in a Drum and Cascade were found to be the best cleaners to remove ground-in dirt and grease.
- Stains may be removed with 45% Isopropanol rubbing alcohol. Do not use higher concentration commercial grades.
- Light surface scratches can be removed by waxing with Simonize paste wax.
- Graffiti may be removed by wiping the affected area with a 1:1 mixture of mineral spirits and undiluted household cleanser such as Mr. Clean or Top Job.

Recommended Cleaners	
Top Job w/Ammonia	Janitor in a Drum
Spic & Span	Cascade
Johnson's Pledge	Handy Andy
Joy Detergent	409
Wisk Detergent	Isopropanol (45%)
Fantastik	All detergent powder
Mr. Clean	Calgonite

Recommended Waxes	
Simonize	Glo-Coat
Aero Wax	

Waxes NOT Recommended	
Plasti Shine	Carnu
Turtle Wax	Body Sheen
Johnson's Pride	

Cleaners NOT Recommended		
All Detergent liquid	Gasoline	Perchloroethylene
Wisk	Methanol	Trichloroethane
Cold Power Liquid	Ethanol	Trichloroethylene
Dynamo	Isopropanol (Greater than 45%)	Aromatic hydrocarbons
Endust	Halogenated Hydrocarbons	Brake Fluid
Lestoil	Isopar K	Butyl Cellusolve
Pine Sol	Hexane	Dupont No. 7 rubbing compound
Gain	Kerosene	
Tetrahydrofuran	Abrasive cleaners	
Cellusolve Acetate	Lighter fluid	